## MODEL SYSTEM I SPECIFICATIONS

Capacity:	10,000 lbs. (4535.92 kg)
Lifting Speed:	50 seconds (faster with lighter load)
Motor Rating:	2.0 HP/208-230V,Single-phase (3ø optional)
Synchronization:	Hydraulic fluid displacement using no chains, cables, or overhead obstructions
Arm Pad Height:	3½" (8.89 cm) min.
Lifting Height:	6' (1.83 m) under arm
Arm Pad Height @ Full Rise:	6' 3½" (1.84 m) min.
Lift Pad Height with Adaptors:	7' ½" (2.15 m)
Overall Width:	11' 10" (3.61 m) ( <b>adjustable</b> )
Width Between Posts:	10' (3.05 m) ( <b>adjustable</b> )
Width Between Lifting Arms:	8' 10" (2.69 m) ( <b>adjustable</b> )
Column Height:	8' 7" (2.62 m)
Overhead Hydraulic Line Height:	12' (3.51 m) Standard ( <b>adjustable</b> to accommodate any height ceiling or routed in-floor)
Weight:	2500 lbs. (1088.62 kg)
Concrete Floor Requirements:	4000 psi (27579.02 kPa) mix 4½" (11.43 cm) depth
Anchoring System: Included	(16) ¾"x5" (1.9x12.7 cm) bolts
Mechanical Safety Locks:	<b>Automatic</b> ; <b>all position</b> starting @ 5" (7.62 cm) off the floor
Hydraulic Safety Systems:	Automatic; all position
Swing Arm Restraints:	Automatic upon ascent
Cylinders:	2 (1 per column)
Drive System:	#646 leaf chain routed over cylinder
3" Frame Adaptors (stackable):	4 included as standard equipment
6" Frame Adaptors (stackable):	4 included as standard equipment
Steel Carriage Bearings:	(8) per carriage, double sealed, self-lubricating
Floor Access Between Posts:	Clear and unobstructed
Warranty:	25 years structural, 10 year mechanical, plus limited lifetime cylinder seal warranty

Mohawk builds the best products with the finest materials, to the highest standards. Just compare our lifts. Our staff will assist you with a fleet evaluation, design assistance and answer any technical questions you have. We invite your calls.

GS2

GSA

contract #GS-07F 207AA

Mohawk lifts are manufactured in compliance with the following standards: ALI, ANSI, ASME, AISI, ASTM, ASA, NEC, AWG, NEMA.

MEETS CURRENT NATIONAL ANSI CODE FOR LIFTS.





Mohawk Resources, LTD. P.O. Box 110 65 Vrooman Ave Amsterdam, NY 12010 (800) 833-2006 (518) 842-1431 FAX: (518) 842-1289 www.mohawklifts.com

AVAILABLE UNDER DISCOUNTED GOVERNMENT CONTRACT IN ALL 50 STATES





HGACBUY.org

105.8 [2.71] 60.6 36.5 MIN [1.54] [.93] 54.7 MAX [1.39] 121.2 [3.08] SHOWN WITH ADJUSTABLE OVERHEAD STEEL HYDRAULIC LINES. 120 [3.05] 84.6 [2.15] 103.1 75.6 [2.62] 3.5 [.09] 72.75 1.85 PAD HEIGH -142.4 [3.62] UNITS: INCHES [METERS] ARCAT BM Specifications subject to change without notice www.mohawklifts.com/specs



Tag to find out more about Mohawk Model System I Lift

For more detailed product information read this book at www.mohawklifts.com/wmamam

**DISTRIBUTED BY:**